

## PASSPORT DATA SHEET

# 200G QSFP-DD



Champion ONE's 200G QSFP-DD optical transceiver is an ideal solution for 200G interconnects, e.g., data center interconnects. It is designed to transmit and receive serial optical data up to 8x25.78Gbps. It can also function as a 2x100G QSFP-DD SR4 transceiver that supports 2x100G connections to two 100G QSFP28 SR4 transceivers using a MPO breakout cable.

*Champion ONE **Passport** transceivers are programmed for universal compatibility across multiple OEM platforms. This open methodology reduces costs and unlocks operational simplicity by reducing sparing costs.*

## Technical Specifications

### STANDARDS AND REGULATORY COMPLIANCE

RoHS 6 compliant  
 QSFP-DD MSA (multi-source agreement)  
 IEEE 802.3bm  
 SFF-8636  
 International Class 1 Laser Safety certified

### APPLICATIONS

200GBase-SR8 Ethernet  
 2x100GBase-SR4 Ethernet

### CONNECTOR

Single MPO24 connector receptacle

### WARRANTY

All feature a limited 3-year warranty

### NOTES

Available in standard temperature (0 to 70°C).  
 Includes DDM functionality

C1 Part Number	Wavelength (nm)	Fiber Type	Rated Distance	Description	Avg. Launch Power per Lane (min/max) (dBm)	Avg. Rx Power per Lane (min/max) (dBm)	Max Power Consumption (W)
<b>200G ETHERNET</b>							
200GQSFPDDE-SR8	850 (8x25.78Gb/s)	MMF	70m (OM3) 100m (OM4)	200G QSFP-DD SR8, 70m (OM3)/100m (OM4) MMF, MPO24 connector, C-Temp	-8.4 / 2.4	-9.5 / 2.4	4.5