

## SUREPORT DATA SHEET

# Calix-Compatible 10G DWDM SFP+



Champion ONE's SFP+ DWDM transceivers offer direct compatibility with existing switches and routers. These optics can be used as part of a passive DWDM solution that enables network operators to cost-effectively expand their fiber capacity.

*Champion ONE Sureport transceivers are programmed for one-to-one compatibility with your existing OEM platforms.*

## Technical Specifications

### STANDARDS AND REGULATORY COMPLIANCE

RoHS compliant  
IEEE Std 802.3ae  
Fibre Channel Draft Physical Interface Specification  
SFP+ MSA (multi-source agreement)  
UL/CSA Class 3862.07 / 3862.87

### PROTOCOLS AND DATA RATES

10G Ethernet  
10G Fibre Channel  
SONET/SDH  
OTU2/OTU2e/OTU3

### DIMENSIONS

8.5 x 13.4 x 56.5 mm ; 75 g

### CONNECTOR

Duplex LC connector

### WARRANTY

All feature a limited 5-year warranty

C1 Part Number	Wavelength (nm)	Fiber Type	Rated Distance (km)	Temp Range (°C)	Description	Tx (min/max) (dBm)	Rx (min/max) (dBm)	Substitute for Calix® part #(s)
<b>MULTI-PROTOCOL 10G (10G LAN/WAN, 10G FC, OC-192, +FEC)</b>								
10GS-Dxx-40(I)-CLX	1528.77 (xx = ch. 61) - 1561.42 (xx = ch. 20)	SMF	40	0 to 70 (-40 to 85)	SFP+ 10GBASE-ER DWDM CHxx 40km, (I-temp) Calix compatible	-1.0 / 3.0	-16.0 / 0.0	
10GS-Dxx-80(I)-CLX	1528.77 (xx = ch. 61) - 1561.42 (xx = ch. 20)	SMF	80	0 to 70 (-40 to 85)	SFP+ 10GBASE-ZR DWDM CHxx 80km, (I-temp), Calix compatible	-1.0 / 4.0	-23.0 / -6.0	

\* Parts are intended as one-to-one replacements. Please verify that the OEM part number is compatible with your system before ordering. If you have questions regarding specific switches and routers, please contact your Champion ONE sales representative for support. In most cases, a customized solution can be developed to meet your needs.

Supported Wavelengths/Channels	Frequency (THz)	Center Wavelength (nm)	ITU Channel	Supported Wavelengths/Channels	Frequency (THz)	Center Wavelength (nm)	ITU Channel	Supported Wavelengths/Channels	Frequency (THz)	Center Wavelength (nm)	ITU Channel	Supported Wavelengths/Channels	Frequency (THz)	Center Wavelength (nm)	ITU Channel
	191.10	1568.77	11		192.40	1558.17	24		193.70	1547.72	37		194.95	1537.79	49.5
	191.15	1568.36	11.5		192.45	1557.77	24.5		193.75	1547.32	37.5		195.00	1537.40	50
	191.20	1597.95	12		192.50	1557.36	25		193.80	1546.92	38		195.05	1537.00	50.5
	191.25	1567.54	12.5		192.55	1556.96	25.5		193.85	1546.52	38.5		195.10	1536.61	51
	191.30	1567.13	13		192.60	1556.55	26		193.90	1546.12	39		195.15	1536.22	51.5
	191.35	1566.72	13.5		192.65	1556.15	26.5		193.95	1545.72	39.5		195.20	1535.82	52
	191.40	1566.31	14		192.70	1555.75	27		194.00	1545.32	40		195.25	1535.43	52.5
	191.45	1565.90	14.5		192.75	1555.34	27.5		194.05	1544.92	40.5		195.30	1535.04	53
	191.50	1565.50	15		192.80	1554.94	28		194.10	1544.53	41		195.35	1534.64	53.5
	191.55	1565.09	15.5		192.85	1554.54	28.5		194.15	1544.13	41.5		195.40	1534.25	54
	191.60	1564.68	16		192.90	1554.13	29		194.20	1543.73	42		195.45	1533.86	54.5
	191.65	1564.27	16.5		192.95	1553.73	29.5		194.25	1543.33	42.5		195.50	1533.47	55
	191.70	1563.86	17		193.00	1553.33	30		194.30	1542.94	43		195.55	1533.07	55.5
	191.75	1563.45	17.5		193.05	1552.93	30.5		194.35	1542.54	43.5		195.60	1532.68	56
	191.80	1563.05	18		193.10	1552.52	31		194.40	1542.14	44		195.65	1532.29	56.5
191.85	1562.64	18.5	193.15	1552.12	31.5	194.45	1541.75	44.5	195.70	1531.90	57				
191.90	1562.23	19	193.20	1551.72	32	194.50	1541.35	45	195.75	1531.51	57.5				
191.95	1561.83	19.5	193.25	1551.32	32.5	194.55	1540.95	45.5	195.80	1531.12	58				
192.00	1561.42	20	193.30	1550.92	33	194.60	1540.56	46	195.85	1530.72	58.5				
192.05	1561.01	20.5	193.35	1550.52	33.5	194.65	1540.16	46.5	195.90	1530.33	59				
192.10	1560.61	21	193.40	1550.12	34	194.70	1539.77	47	196.95	1529.94	59.5				
192.15	1560.20	21.5	193.45	1549.72	34.5	194.75	1539.37	47.5	196.00	1529.55	60				
192.20	1559.79	22	193.50	1549.32	35	194.80	1538.98	48	196.05	1529.16	60.5				
192.25	1559.39	22.5	193.55	1548.91	35.5	194.85	1538.58	48.5	196.10	1528.77	61				
192.30	1558.98	23	193.60	1548.51	36	194.90	1538.19	49	196.15	1528.38	61.5				
192.35	1558.58	23.5	193.65	1548.11	36.5										