

## SUREPORT DATA SHEET

# CALIX-Compatible Dual Fiber SFP



Champion ONE's Dual Fiber SFP product line supports a variety of protocols over a wide range of distance and temperature options. These optics are fully MSA-compliant and offer direct compatibility with your existing switches and routers.

*Champion ONE Sureport transceivers are programmed for one-to-one compatibility with your existing OEM platforms.*

## Technical Specifications

### STANDARDS AND REGULATORY COMPLIANCE

RoHS compliant  
SFP MSA (multi-source agreement)  
IEEE Std 802.3  
Fibre Channel Draft Physical Interface Specification  
Compliant with SONET/SDH optical standards  
UL/CSA Class 3862.07 / 3862.87

### PROTOCOLS AND DATA RATES

Fast Ethernet (125Mbps)  
Gigabit Ethernet (1.25Gbps)  
SONET OC-3/OC-12/OC-48  
Fibre Channel (1G, 2G, 4G)

### DIMENSIONS

8.5 x 13.4 x 56.5 mm ; 75 g

### CONNECTOR

Duplex LC connector

### WARRANTY

All feature a limited 5-year warranty

C1 Part Number	Transmit Wavelength (nm)	Fiber Type	Rated Distance (km)	Temp Range (°C)	Description	Tx (min/max) (dBm)	Rx (min/max) (dBm)	Substitute for Calix® part #s
<b>GIGABIT ETHERNET (1.25 GBPS), 1G FIBRE CHANNEL (1.0625 GBPS)</b>								
GESFP-SXI-CLX	850	MMF	0.55	-40 to 85	SFP 1000Base-SX 550m, I-temp, Calix compatible	-9.0 / -3.0	-18.0 / 0.0	100-01660
GESFP-LXI-CLX	1310	SMF	10	-40 to 85	SFP 1000Base-LX 10km, I-temp, Calix compatible	-9.0 / -3.0	-19.0 / -3.0	100-01662
GESFP-EXI-CLX	1310	SMF	40	-40 to 85	SFP 1000Base-EX 40km, I-temp, Calix compatible	-5.0 / 0.0	-24.0 / -1.0	100-01663
GESFP-ZXI-CLX	1550	SMF	80	-40 to 85	SFP 1000Base-ZX 80km, I-temp, Calix compatible	0.0 / 5.0	-26.0 / -3.0	100-01664
GESFP-VX-CLX	1550	SMF	120	0 to 70	SFP 1000Base-VX 120km, Calix compatible	0.0 / 5.0	-32.0 / -10.0	N/A

\* Parts are intended as one-to-one replacements. Please verify that the OEM part number is compatible with your system before ordering. If you have questions regarding specific switches and routers, please contact your Champion ONE sales representative for support. In most cases, a customized solution can be developed to meet your needs.