

SUREPORT DATA SHEET

Nokia/ALU-Compatible DWDM XFP



Our standard fixed channel DWDM XFPs are available in over 40 standard ITU DWDM channels (channels 20-61— see the table on page 2 for specifics). They are multi-rate, capable of supporting 10G Ethernet for LAN and WAN, SONET OC-192, as well as 10G Fibre Channel. They also support FEC (if enabled by the port). Our carrier-grade DWDM XFP transceivers feature digital diagnostics, also known as digital optical monitoring (DOM), which is fully supported by Nokia/ALU® and other major carriers.

Champion ONE Sureport transceivers are programmed for one-to-one compatibility with your existing OEM platforms.

Technical Specifications

STANDARDS AND REGULATORY COMPLIANCE

RoHS compliant
IEEE Std 802.3ae
Fibre Channel Draft Physical Interface Specification
Compliant with SONET/SDH optical standards
XFP MSA (multi-source agreement)
UL/CSA Class 3862.07 / 3862.87

PROTOCOLS AND DATA RATES

SONET OC-192
10G Ethernet LAN/WAN
10G Fibre Channel
ITU-T G.709
10GBASE LAN/WAN + FEC
10G FC and FEC

DIMENSIONS

71 x 18.5 x 8.5 mm ; 300 g

CONNECTOR

Duplex LC connector

WARRANTY

All feature a limited 5-year warranty

C1 Part Number	Transmit Wavelength (nm)	Fiber Type	Rated Distance (km)	Temp Range (°C)	Description	Tx (min/max) (dBm)	Rx (min/max) (dBm)	Substitute for Nokia/ALU® part #
MULTI-PROTOCOL 10G (10G LAN/WAN, 10G FC, OC-192, +FEC)								
10GX-Dxx-80(l)-ALU	1528.77 (ch. 61) to 1561.42 (ch. 20)	SMF	80	0 to 70 (-40 to 85)	XFP 10GBASE-DWDM CHxx 80km, multi-rate, Nokia/ALU compatible	-1.0 / 5.0	-24.0 / -6.0	XFP-DWDM

* Parts are intended as one-to-one replacements. Please verify that the OEM part number is compatible with your system before ordering. If you have questions regarding specific switches and routers, please contact your Champion ONE sales representative for support. In most cases, a customized solution can be developed to meet your needs.

Supported Wavelengths/Channels	Frequency (THz)	Center Wavelength (nm)	ITU Channel	Supported Wavelengths/Channels	Frequency (THz)	Center Wavelength (nm)	ITU Channel	Supported Wavelengths/Channels	Frequency (THz)	Center Wavelength (nm)	ITU Channel	Supported Wavelengths/Channels	Frequency (THz)	Center Wavelength (nm)	ITU Channel
	191.10	1568.77	11		192.40	1558.17	24		193.70	1547.72	37		194.95	1537.79	49.5
	191.15	1568.36	11.5		192.45	1557.77	24.5		193.75	1547.32	37.5		195.00	1537.40	50
	191.20	1597.95	12		192.50	1557.36	25		193.80	1546.92	38		195.05	1537.00	50.5
	191.25	1567.54	12.5		192.55	1556.96	25.5		193.85	1546.52	38.5		195.10	1536.61	51
	191.30	1567.13	13		192.60	1556.55	26		193.90	1546.12	39		195.15	1536.22	51.5
	191.35	1566.72	13.5		192.65	1556.15	26.5		193.95	1545.72	39.5		195.20	1535.82	52
	191.40	1566.31	14		192.70	1555.75	27		194.00	1545.32	40		195.25	1535.43	52.5
	191.45	1565.90	14.5		192.75	1555.34	27.5		194.05	1544.92	40.5		195.30	1535.04	53
	191.50	1565.50	15		192.80	1554.94	28		194.10	1544.53	41		195.35	1534.64	53.5
	191.55	1565.09	15.5		192.85	1554.54	28.5		194.15	1544.13	41.5		195.40	1534.25	54
	191.60	1564.68	16		192.90	1554.13	29		194.20	1543.73	42		195.45	1533.86	54.5
	191.65	1564.27	16.5		192.95	1553.73	29.5		194.25	1543.33	42.5		195.50	1533.47	55
	191.70	1563.86	17		193.00	1553.33	30		194.30	1542.94	43		195.55	1533.07	55.5
	191.75	1563.45	17.5		193.05	1552.93	30.5		194.35	1542.54	43.5		195.60	1532.68	56
	191.80	1563.05	18		193.10	1552.52	31		194.40	1542.14	44		195.65	1532.29	56.5
191.85	1562.64	18.5	193.15	1552.12	31.5	194.45	1541.75	44.5	195.70	1531.90	57				
191.90	1562.23	19	193.20	1551.72	32	194.50	1541.35	45	195.75	1531.51	57.5				
191.95	1561.83	19.5	193.25	1551.32	32.5	194.55	1540.95	45.5	195.80	1531.12	58				
192.00	1561.42	20	193.30	1550.92	33	194.60	1540.56	46	195.85	1530.72	58.5				
192.05	1561.01	20.5	193.35	1550.52	33.5	194.65	1540.16	46.5	195.90	1530.33	59				
192.10	1560.61	21	193.40	1550.12	34	194.70	1539.77	47	196.95	1529.94	59.5				
192.15	1560.20	21.5	193.45	1549.72	34.5	194.75	1539.37	47.5	196.00	1529.55	60				
192.20	1559.79	22	193.50	1549.32	35	194.80	1538.98	48	196.05	1529.16	60.5				
192.25	1559.39	22.5	193.55	1548.91	35.5	194.85	1538.58	48.5	196.10	1528.77	61				
192.30	1558.98	23	193.60	1548.51	36	194.90	1538.19	49	196.15	1528.38	61.5				
192.35	1558.58	23.5	193.65	1548.11	36.5										