



AOC DATA SHEET

10G Active Optical Cables

Champion ONE's 10G Active Optical Cables (AOCs) fill the need for short, cost-effective connectivity. In high-capacity interconnections, AOCs provide a power-efficient, easy-to-use replacement for optical transceivers and fiber jumper cables. These AOCs are fully compliant with EEPROM and memory map requirements to ensure proper system identification and interoperability.

Champion ONE offers both straight SFP+ and breakout cables with 4x10G SFP+ optics at one end for breakout/aggregation applications.

Technical Specifications

STANDARDS AND REGULATORY COMPLIANCE RoHS compliant IEEE802.3ae SFP+ MSA (SFF 8431)

PROTOCOLS AND DATA RATES 10G Ethernet 4G/8G Fibre Channel Infiniband QDR, DDR, SDR

DIMENSIONS

LxWxH (mm): 58.4 (122 incl. pull ring) x 13.5×8.5 1m to 100m multimode fiber

CONNECTOR

Cables terminate with their respective form factors.

WARRANT\

All feature a limited lifetime warranty.

NOTES

See page 2 for programming compatibility capabilities.

| C1 Part Number ¹ | Transmit Wavelength (nm) | Fiber Type | Standard Rated Distance (m) ² | Temp Range (°C) | Description | Max Power Consumption (W) | |
|--------------------------------|--------------------------------|---------------|---|--------------------|--|-------------------------------|--|
| 10G ETHERNET | | | | | | | |
| CAB-SFP+-SFP+-AOC-xM-C1 | 850 | MMF | x = 1,2,3,5,10,20,30,50,100 | 0 to 70 | SFP+ to SFP+ Active Optical Cable, xx meters | 1.0 | |
| 40G ETHERNET TO 4X10G ETHERNET | | | | | | | |
| CAB-QSFP-4XSFP-AOC-xM-C1 | 850 | MMF | x = 1,2,3,4,5,6,7,8,9,10,20,30 | 0 to 70 | QSFP+ to 4xSFP+ Breakout Active Optical Cable, xx meters | 0.8 (per SFP+) 1.5 (QSFP+) | |

^{1.} These part numbers are for Passport universal cables, which can be used across multiple platforms and open systems. For programmed options, please refer to page 2.

^{2.} Custom lengths are available in whole meter increments between the standard minimum and maximum length.



Ordering Information: Programmed Cables

To order a cable programmed for use in a specific system, simply add "-C1" to the end of your network platform part number. For example, to order a 3m AOC programmed for 100% Cisco compatibility, your C1 part number will be SFP-10G-AOC3M-C1.

The technical specifications listed on page 1 will be the same for all programmed options.

Ordering Information: Multi-Vendor Programmed Cables

For multi-vendor environments that require programming for one-to-one compatibility, please use the following scheme:

PART NUMBER SCHEMES:

SFP10G-XX₁XX₂-AOC-YM-C1 Q40X10G-XX₁XX₂-AOC-YM-C1

| XX_N | Vendor Brand | | |
|--------|--------------|----|-------------|
| AC | Accedian | F5 | F5 Networks |
| AD | Adtran | FN | Fortinet |
| AL | Alcatel | HP | HP |
| AN | Arista | IB | IBM |
| AR | Aruba | IN | Intel |
| AV | Avaya | JN | Juniper |
| ВС | Broadcom | LN | Lenovo |
| BR | Brocade | MK | Meraki |
| CX | Calix | MX | Mellanox |
| CS | Cisco | NP | NetApp |
| CD | Cohesity | NX | Nutanix |
| DF | Dell | PA | Palo Alto |
| EN | Enterasys | RB | Rubrik |
| EX | Extreme | XN | Xilinx |

| Υ | Cable Length | | | |
|-----|--------------|--|--|--|
| 50C | 50 cm | | | |
| 1 | 1 m | | | |
| 2 | 2 m | | | |
| 3 | 3 m | | | |
| 4 | 4 m | | | |
| 5 | 5 m | | | |
| 6 | 6 m | | | |
| 7 | 7 m | | | |
| 8 | 8 m | | | |
| 9 | 9 m | | | |
| 10 | 10 m | | | |