



100G Direct Attach Cables

Champion ONE's 100G Direct Attach Cables (DACs) fill the need for shortrange, cost-effective connectivity. In high-capacity server connections, DACs provide a power-efficient, easy-to-use replacement for optical transceivers and cables. These cables are fully compliant with EEPROM and memory map requirements to assure proper system identification and interoperability.

Champion ONE offers both straight QSFP28 and breakout cables with 4x25G SFP28 modules at one end for breakout/aggregation applications.

Technical Specifications

STANDARDS AND REGULATORY COMPLIANCE

RoHS compliant IEEE802.3bj QSFP28 MSA SFP28 MSA

PROTOCOLS AND DATA RATES

100G Ethernet (103.125 Gbps) 25G Ethernet (breakout only)

DIMENSIONS

LxWxH (mm): 72 (122 incl. pull ring) x 18.4 x 8.5 0.5m to 5m Copper Cable (24 to 30 AWG) **CONNECTOR** Cables terminate with their respective form factors.

WARRANTY All feature a limited lifetime warranty.

NOTES

See page 2 for programming compatibility capabilities.

| C1 Part Number ¹ | Cable Type | Cable Gauge | Rated Distance (m) | Temperature Range (°C) | Description | Max Power Consumption (W) |
|---------------------------------|------------|--------------------------|--|---------------------------|---|---------------------------------|
| 100G ETHERNET TO 100G ETHERNET | | | | | | |
| CAB-QSFP-100G-DACP-xM-C1 | Passive | 24-30AWG Copper Cable | 0.5 / 1 / 2 / 3 / 4 / 5 (x = 50C / 1 / 2 / 3 / 4 / 5) | 0 to 70 | 100G QSFP28 to QSFP28 Direct Attach Cable, 0.5 to 5m | 0.5 |
| 100G ETHERNET TO 4X25G ETHERNET | | | | | | |
| CAB-QSFP28-4SFP25G-CUxM-C1 | Passive | 24-30AWG Copper Cable | 0.5/1/2/3/4/5 | 0 to 70 | 100G QSFP28 to 4x25G SFP28 Breakout Direct Attach Cable, 0.5 to 5m | 0.5 |

1. These part numbers are for Passport universal cables, which can be used across multiple platforms and open systems. For programmed options, please refer to page 2.



Ordering Information: Programmed Cables

To order a cable programmed for use in a specific system, simply add "-C1" to the end of your network platform part number. For example, to order a 3m DAC programmed for 100% Cisco compatibility, your C1 part number will be QSFP-100G-CU3M-C1.

The technical specifications listed on page 1 will be the same for all programmed options.

Ordering Information: Multi-Vendor Programmed Cables

For multi-vendor environments that require programming for one-to-one compatibility, please use the following schemes:

PART NUMBER SCHEME:

QSFP100G-XX₁XX₂-CU-YM-C1 Q100X25G-XX₁XX₂-CU-YM-C1

| XX _N | Vendor Brand | | |
|-----------------|--------------|----|-------------|
| AC | Accedian | F5 | F5 Networks |
| AD | Adtran | FN | Fortinet |
| AL | Alcatel | ΗP | HP |
| AN | Arista | IB | IBM |
| AR | Aruba | IN | Intel |
| AV | Avaya | JN | Juniper |
| BC | Broadcom | LN | Lenovo |
| BR | Brocade | MK | Meraki |
| CX | Calix | MX | Mellanox |
| CS | Cisco | NP | NetApp |
| CD | Cohesity | NX | Nutanix |
| DF | Dell | PA | Palo Alto |
| EN | Enterasys | RB | Rubrik |
| ΕX | Extreme | XN | Xilinx |

| Y | Cable Length | | | |
|-----|--------------|--|--|--|
| 50C | 50 cm | | | |
| 1 | 1 m | | | |
| 2 | 2 m | | | |
| 3 | 3 m | | | |
| 4 | 4 m | | | |
| 5 | 5 m | | | |