

PASSIVES DATA SHEET



40 Channel Dual Fiber DWDM Mux/ Demux ITU Ch. 21 – 60 + 1310nm Channel

Champion ONE's DWDM passive networking products for inside-plant applications provide a cost-effective, high-reliability solution to fiber capacity challenges.

Technical Specifications

WAVELENGTH INFORMATION

DWDM channel wavelengths: ITU Ch. 21 – 60, 100GHz spacing
 MON operating wavelength: 1260–1620nm
 Passband width: ITU ± 0.11nm

FORM FACTOR AND CONNECTOR TYPES

LC/UPC connector (all ports)

DIMENSIONS (LXWXH)

Body: 250 x 440 x 44 mm
 Faceplate: 482.6 x 44mm

TEMPERATURE RANGE

-10° C to 75° C (operating)
 -40° C to 85° C (storage)

WARRANTY

All feature a limited 5-year warranty

COMPLIANCES

RoHS compliant
 Telcordia GR-1209, GR-1221

Parameter	Value
DWDM Channel Insertion Loss (dB)	≤ 6.3
MON Port Insertion Loss (mux/demux, dB)	≤ 25.3 / 19.0
Passband Ripple (dB)	≤ 0.5
Adjacent Channel Isolation between DWDM Channels (dB)	≥ 30
Non-Adjacent Channel Isolation Between DWDM Channels (dB)	≥ 40

Parameter	Value
Polarization Dependent Loss (dB)	≤ 0.2
Directivity (dB)	≥ 50
Return Loss (dB)	≥ 45
Polarization Mode Dispersion (ps)	≤ 0.2
Fiber Type	SMF-28e+ 900 μm
Max Power Handling (mW)	300

Ordering Information

C1 Part Number	Description
ZS-DWDM-M/D-100-40-L-8-0-21-R	DWDM M/D 100GHz 40 Chl, LC, no skips, Ch 21 start, 2% Mon, 1310PB, 1RU

Network Diagram

