



SUREPORT DATA SHEET

## Cisco-Compatible 10G Single Fiber XFP

Champion ONE's XFP single fiber bi-directional (bidi) product line enables you to double network capacity without running new fiber. By utilizing a single strand of fiber for full-duplex circuits, our bidi solutions help you reduce test, turn up, and fiber lease costs.

Champion ONE **Sureport** transceivers are programmed for one-to-one compatibility with your existing OEM platforms.

## **Technical Specifications**

STANDARDS AND REGULATORY COMPLIANCE ROHS compliant XFP MSA (multi-source agreement)

PROTOCOLS AND DATA RATES
Product line supports the following protocols and data rates:
10G Ethernet LAN/WAN
10G Fibre Channel
SONET/SDH
OTU2/OTU2e/OTU3

CONNECTOR Simplex LC connector

WARRANTY
All feature a limited 5-year warranty

NOTES
A Champion ONE exclusive product.

C1 Part Number	Wavelength (nm)	Fiber Type	Rated Distance (km)	Temp Range (°C)	Description	Tx (min/max) (dBm)	Rx (min/max) (dBm)	Substitute for Cisco® part #s
10G ETHERNET/FIBRE CHANNEL/SONET/SDH/OTU2/OTU2E/OTU3								
10GX-Bxx-10-CSC	1270 Tx/ 1330 Rx (xx=27) 1330 Tx/ 1270 Rx (xx=33)	MMF	10	0 to 70	XFP SF 10GBase-LR 1xx0nm Tx, 10km, Cisco Systems compatible	-5.0 / 0.0	-14.0 / 0.5	***C1 Exclusive***
10GX-Bxx-40-CSC	1270 Tx/ 1330 Rx (xx=27) 1330 Tx/ 1270 Rx (xx=33)	SMF	40	0 to 70	XFP SF 10GBase-ER 1xx0nm Tx, 40km, Cisco Systems compatible	0.0 / 6.0	-14.0 / 0.5	***C1 Exclusive***
10GX-Bxx-60-CSC	1270 Tx/ 1330 Rx (xx=27) 1330 Tx/ 1270 Rx (xx=33)	SMF	60	0 to 70	XFP SF 10GBase-ER 1xx0nm Tx, 60km, Cisco Systems compatible	0.0 / 5.0	-18.0 / -5.0	***C1 Exclusive***
10GX-Bxx-80-CSC	1490 Tx/ 1550 Rx (xx=49) 1550 Tx/ 1490 Rx (xx=55)	SMF	80	0 to 70	XFP SF 10GBase-ZR 1xx0nm Tx, 80km, Cisco Systems compatible	0.0 / 5/0	-24.0 / -6.0	***C1 Exclusive***

<sup>\*</sup> Parts are intended as one-to-one replacements. Please verify that the OEM part number is compatible with your system before ordering. If you have questions regarding specific switches and routers, please contact your Champion ONE sales representative for support. In most cases, a customized solution can be developed to meet your needs.